

# CRL290 SERIES TOP HUNG SLIDING DOOR SYSTEM WITH SOFTBRAKE BRAKING SYSTEM

- Systems Available for Wall, Ceiling, or Dropped Ceiling Applications, With or Without Fixed Panels
- Can Accommodate Doors Weighing Up to 264 Pounds (120 kg)
- Clamps are Fully Concealed Inside the Header
- Integrated Softbrake Braking System
- For Use With 5/16", 3/8" or 1/2" (8, 10 or 12 mm) Tempered Glass
- No Notches or Holes Required in the Glass for Installation

The **CRL290 Series Top Hung Sliding Door Systems** are a stouter version of our tremendously popular CRL285 Series, allowing for panels weighing up to 264 pounds (120 kg). This new series also has an improved Softbrake Braking System that can stand up to the demands of door panels at the heavier weight, ensuring that you do not have to worry about the doors slamming open or closed! Softbrake cushions the opening and closing of the doors gently, quietly, and is completely concealed inside the header. Softbrake engages during the last 4" (100 mm) of door travel, preventing the glass from impacting the frame or adjacent glass panel.

The **CRL290 Series** offers multiple mounting options, is top hung, requires no bottom track, and operates with smooth, fingertip control. No holes or notches required, making glass fabrication easy and cost effective. The upper clamp and roller assemblies have over 1/4" (6 mm) of height adjustment during installation, allowing for easy correction of openings that are not true and level. Kits are available in satin anodized and brushed nickel anodized finishes.



**CRL**<sup>®</sup>  
ALUMINUM

**C.R. LAURENCE COMPANY**

[crlaurence.com](http://crlaurence.com) | [usalum.com](http://usalum.com) | [crl-arch.com](http://crl-arch.com)

Phone: (800) 421-6144 Ext. 7700 | Email: [architectural@crlaurence.com](mailto:architectural@crlaurence.com)