

TRANSPARA™

VERTICALLY FRAMELESS SHOWER DOOR SYSTEM

NEW!

- Doors Shipped “Ready-to-Install” With Door Rails Factory Bonded to 3/8” (10 mm) Thick Tempered Glass
- Doors Rise 1/8” (3 mm) for Quiet Bottom Seal Operation
- Plus or Minus 1” (25 mm) Door Closing Position Adjustment
- Water Management System in Bottom Pivot, and SDTW Vinyl Wipe Integrated Into Door Rail
- Ceiling/Soffit Mount or Header Mount Options Available
- Stock Door Kit or Custom Door Systems Offered
- Stock Doors Prepped With Holes and Supplied With BM6X6 Model Handle
- Fixed Panels Can Be Supplied by CRL or Customer
- Stocked in Four Popular Finishes

The **NEW Transpara™ Shower Door System** offers a truly all-glass aesthetic by being able to handle large glass lites without the need for door hinges or vertical framing. This produces uninterrupted glass visuals that are further enhanced by sleek, low-profile door rails. Matching U-Channel on adjacent fixed panels, maintain a continuous sightline across the entire enclosure. With visible hardware being only 3/4” (19 mm) high, Transpara™ delivers the best in contemporary design.

Appearances can be deceiving; despite having minimal hardware, the thin frames come equipped with innovative performance features. They include a water management system that is integrated into the closing mechanism, and a four-component fitting that uses the weight of the door itself to close. The installer-friendly door comes factory pre-glazed, and requires only two screws to install the bottom pivot.



TRANSPARA™

PATENT PENDING

Vertically Frameless Shower Door System

STOCK FINISHES:



MODEL TRA2884

READY-TO-INSTALL STOCK DOOR KIT

28" X 84" (711 X 2134 MM)

INCLUDES:

- Top Pivot
- Bottom Pivot Set with Mounting Fasteners and Expansion Anchors
- Top and Bottom Rails Bonded Onto the 3/8" (10 mm) Glass Door, with Bushing Pre-installed in the Top Rail, and Pivot Pin and Self-Closing Mechanism in the Bottom Rail
- Four End Caps Bonded Into Place
- BM6X6 Model Tubular Back-to-Back Pull Handle



ITEMS ORDERED SEPARATELY:

- Fixed Panel Glass
- TRA1516UC Fixed Panel U-Channel
- TRAUCEC1 U-Channel End Caps
- Vertical Seals
- SQH980 Header and TRAHPR1 Pivot Retainer Block (if necessary)

MODEL TRAC1

CUSTOM TRANSPARA™ SYSTEM:

Please allow CRL to assist you by constructing a Custom Transpara™ Vertically Frameless Shower Door System. By submitting a drawing of the enclosure opening, complete with dimensions, angles, out of square, out of level, and other pertinent information, our Shower Door Technical Department can work to create a quotation for your review. Please email your drawing to showers@crlaurence.com, or for questions please contact us at (800) 421-6144 in the U.S., (877) 421-6144 from Canada, or (323) 588-1281 Internationally, and ask for our Shower Door Technical Department at ext. 7740.

SPECIFICATIONS:

Door Glass Thickness:

3/8" (10 mm) Tempered Safety Glass

Construction: Extruded Aluminum

Door Swing: Full Rotation

Closing Type: Self Closing When Within 45 Degrees of Closed Position
No Cut-Out Required

MAXIMUM CAPACITIES:

Door Weight: 100 lbs/45 kg

Door Width: 31"/787 mm

(Do not exceed either Door Weight or Door Width)

AVDB4238_05/16



C.R. LAURENCE COMPANY

crlaurence.com | usalum.com | crl-arch.com

Phone: (800) 421-6144 Ext. 7740 | Email: showers@crlaurence.com