

Mirror Mastic - Product Cross Reference Chart

5/14/2002

PRODUCT	CATALOG NUMBER	CONTAINER SIZE	MASTIC COLOR	APPLICATIONS	INSTALLATION GUIDELINES	SUBSTRATE LIMITATIONS	CURE TIME
CRL HEAVY BODIED MIRROR MASTIC	600QT 600GL	QUART CANS GALLON CANS	BLACK	PLATE GLASS MIRROR, SLATE, SYNTHETIC BLACKBOARDS, BUILDING PANELS	FULL COVERAGE WITH TROWEL, "GOBS"	PRIME POROUS SUBSTRATES, REMOVE PAINT & WALLPAPER	30 - 45 DAYS
CRL LIGHT BODIED MIRROR MASTIC	300QT 300GL	QUART CANS GALLON CANS	BLACK	PLATE GLASS MIRROR	FULL COVERAGE	PRIME POROUS SUBSTRATES, REMOVE PAINT & WALLPAPER	30 - 45 DAYS
PALMER REGULAR MIRRO-MASTIC	PM601T PM601QT	11 FL. OZ. TUBE 29 FL. OZ. TUBE	BLACK	PLATE GLASS MIRROR, ACRYLIC MIRROR, CATEGORY II SAFETY TAPE	GOLF BALL SIZE PATS	PRIME POROUS SUBSTRATES, REMOVE PAINT & WALLPAPER	30 - 60 DAYS
	PM204QT PM201GL PM205	QUART CANS GALLON CANS 5 GALLON PAILS					30 - 45 DAYS
PALMER QWIKSET MIRRO-MASTIC	PM711N	11 FL. OZ. TUBE	BLACK	PLATE GLASS MIRROR NOT FOR ACRYLIC MIRROR OR CAT. II SAFETY TAPE	VERTICAL BEADS OR PATS	PRIME POROUS SUBSTRATES, REMOVE PAINT & WALLPAPER	80% STRENGTH IN 48 HOURS
GUNTHER ULTRA/BOND MIRROR MASTIC	GN100A GN101B	10.1 FL OZ TUBE GALLON CANS	CREAM	PLATE GLASS MIRROR NOT FOR ACRYLIC MIRROR OR CAT. II SAFETY TAPE	VERTICAL BEADS 4 - 5" SPOTS	PRIME POROUS SUBSTRATES, REMOVE PAINT & WALLPAPER	30% STRENGTH IN 24 HOURS FULL 28 DAYS
GUNTHER EXTRA/BUILD MIRROR MASTIC	GN200A GN201B	10.1 FL OZ TUBE GALLON CANS	BLACK	PLATE GLASS MIRROR NOT FOR ACRYLIC MIRROR OR CAT. II SAFETY TAPE	4 - 5" SPOTS	PRIME POROUS SUBSTRATES, REMOVE PAINT & WALLPAPER	20% STRENGTH IN 48 HOURS FULL 30 DAYS
GUNTHER PREMIER MIRROR MASTIC	GN104A	10.3 FL OZ TUBE	GRAY	PLATE GLASS MIRROR, ACRYLIC MIRROR, CATEGORY II SAFETY TAPE	3" SPOTS	REMOVE PAINT & WALLPAPER. POROUS OR NON-POROUS SUBSTRATES, AND PRIMED OR UN-PRIMED SUBSTRATES ARE O.K.	30% STRENGTH IN 24 HOURS FULL 7 DAYS
PRIMERS: PALMER MIRRO-MASTIC BOND	PM401QT PM401GL	QUART CANS GALLON CANS	FLAT BLACK	REGULAR PALMER MIRRO-MASTIC AND CRL 300 & 600 SERIES MASTIC. DO NOT USE WITH QWIKSET.	100 SF PER QT 400 SF PER GL		APPROX. 3 - 4 HRS. DRY TIME
GUNTHER PRIME-N-SEAL PRIMER	GN6	GALLON CANS	FLAT WHITE	GUNTHER ULTRA/BOND, EXTRA/BUILD & PREMIER	400 SF PER GL		APPROX. 30 MIN. DRY TIME

Test before using any mastic! Always follow manufacturer's directions on the container. Do not apply to a painted surface, wall covering or treated wood. Support mirror at bottom. The use of mechanical fasteners is recommended for all mirror applications, such as CRL Mirror Clips, or with CRL Mirror Mounting Tape. Apply both double-sided mirror mounting tape and mastic at room temperature. If the directions do not cover conditions at hand, consult CRL Technical Sales. It is the users responsibility to determine the mastic's suitability to a particular application. CRL cannot guarantee materials against mirror spoilage. We do not recommend using any mastic for ceiling mirror installation without using mechanical fasteners. If you have questions concerning the use of mastics, call CRL Technical Sales for more information.