




**C.R. LAURENCE CO., INC.**  
**PROFESSIONAL QUALITY**



# PETITE

180° Glass to Glass Hinge (Door Swings 180° In Only)

CAT No. PET182

| *Maximum Door Capacities | 1/4" (6mm)     |            | 5/16" (8mm)    |            |
|--------------------------|----------------|------------|----------------|------------|
|                          | Weight         | Width      | Weight         | Width      |
| Using 2 Hinges           | 55 lbs.(25 kg) | 31"(787mm) | 55 lbs.(25 kg) | 31"(787mm) |
| Using 3 Hinges           | 82 lbs.(37 kg) | 34"(864mm) | 82 lbs.(37 kg) | 34"(864mm) |

\*NOTE: Do not exceed either maximum weight or width when choosing proper quantity of hinges.

## Important Information:

Door and fixed panel use the same hole pattern.

## Specifications:

**Glass Sizes:** 1/4" (6mm) to 5/16" (8mm) thick tempered safety glass

**Construction:** Solid brass

**Closing Type:** Self-centering when within 15° of closed position

**Cutout Required**

**Includes:** Gaskets, screws and template

## Use of Gaskets:

**For 1/4"(6mm) Glass:** Use one thick gasket on each side

**For 5/16"(8mm) Glass:** Use one thin gasket on each side

## Recommendations:

For public safety, we recommend the use of only tempered safety glass.

Do not use power tools when installing these hinges.

## Maintenance Guidelines:

- Never use an abrasive cleaner on the hardware. Many of the components are coated with a clear lacquer that will be irreparably damaged if subjected to harsh, abrasive chemicals. Advise your customer that drying the hardware with a clean, soft towel on a daily basis is the best way to maintain the hardware. If mineral deposits build-up, mix a couple of drops of a mild liquid soap (such as Ivory or a similar product) into a cup of warm water. Using a soft, non-abrasive cloth, clean the hardware. Rinse thoroughly with clean, warm water and dry.